OVER YEARS



Λ Legacy of Innovation, Λ New Era of Discovery

Celestron Origin stands at the forefront of a new era in amateur astronomy, blending stargazing and astrophotography into a single, user-friendly experience. This intelligent, all-in-one home observatory takes the complexity out of traditional telescopes, transforming your backyard into a gateway to the cosmos. Packed with cutting-edge technology, Celestron Origin captures the beauty of celestial objects and brings them to life on your phone or tablet.

Learn more at celestron.com/origin



OPTICAL DESIGN	Rowe-Ackermann Schmidt Astrograph (RASA)	
APERTURE	152mm	
FOCAL LENGTH	335mm	
EFFECTIVE FOCAL RATIO	f/2.2	
OPTICAL COATINGS	StarBright XLT coatings throughout	
FILTER DRAWER	Integrated, accepts 1.25" or 2" astroimaging filters	

D 46122

HD 4

HD 47072

HD 46748


HD 46301

a

 $7 \mathbf{Q}^2$

i R HD 47339 HD 46947 HD 46966 Mon V649 Mon HD 47107

Ready To Image



CMOS IMAGE SENSOR	Sony IMX178LQJ, color, back-illuminated
SENSOR SIZE	8.92mm diagonal
PIXEL SIZE	2.4µm x 2.4µm
NUMBER OF EFFECTIVE PIXELS	6.44M (3096 x 2080)
FIELD OF VIEW	1.27° x 0.85°



ONBOARD COMPUTER	Raspberry Pi 4 Model B	
MOUNT	Computerized GoTo altazimuth mount	
DEW PREVENTION	Fully automated heating element integrated into front lens, removable dew shield/lens shade	
FOCUS MOTOR	Autofocus or manual control	
COOLING FANS	One (1) fan for optics, one (1) fan for electronics, both pull air though vents with wire mesh	
LED STATUS RING	Indicates status "at-a-glance"	





Λ Legacy of Innovation, Λ New Era of Discovery

PORTS	USB-A	Two (2) on optical tube for accessing raw image files for external processing, one (1) on mount for mobile device charging only
	ETHERNET	One (1) on optical tube
	AUXILIARY PORTS	Two (2) on optical tube, four (4) on mount
)	
POWER	BATTERY	Integrated LiFePO4, 97.9 Wh, capable of 6+ hours of use
	POWER INPUT	12V DC adapter for charging internal battery or running on external AC power
	CELESTRON ORIGIN APP	Runs on compatible iOS or Android smartphones and tablets
	SYSTEM REQUIREMENTS	iOS 16 or higher, Android 12 or higher
	OPTICAL TUBE	24" x 7" diameter
	MOUNT	18" x 12" x 10"
	TRIPOD (COLLAPSED)	13" x 12" x 32"
	ASSEMBLED SYSTEM	24" L x 26" W x 48" H
WEIGHT		
	OPTICAL TUBE	10.6 lb
<u>_</u>	MOUNT	17.0 lb
	TRIPOD	14.0 lb
	TOTAL SYSTEM	41.6 lb

Inverkehrsbringer und Service für Deutschland und Osterreich: Baader Planetarium GmbH – Zur Sternwarte - 82291 Mammendorf Tel.: 08145/80890 - service@celestron-deutschland.de